



Product Specification

PS001855

Revision No: NEW ISSUE

Date: 06/12/2015

CALIBER: 5.56mm

CARTRIDGE: M200 Blank

Manufactured to U.S. Military Specifications:

- MIL-DTL-60616
- MIL-STD-636
- MIL-STD-1916
- Drawing: 10542379



Warning: Blank cartridges depend on the weapon system and Blank Firing Adapter (BFA) to create the correct pressure to operate the weapon. M200 cartridge testing can be performed with the following weapon/BFA combinations:

- M16A2 Weapon/M15A2 BFA
- M249 Weapon/M15A2 or 12598135 BFA
- M4 Weapon/M23 BFA
- M16A1 Weapon/M15A2 BFA

The use of any other weapon/BFA combination is not recommended and can result in extreme overpressure or insufficient pressure to operate the weapon.

CASE: Identification Knurl, Brass (Copper Alloy No. 260)

PRIMER: No. 41 Boxer Style

TIP ID: Purple Lacquer

Operating Range: -32°C to 52 °C
(-25 °F to 125 °F)

PRIMER SEALANT: Yes

CASE MOUTH SEALANT: Yes

HEADSTAMP: LC manufacturer symbol and the year of manufacture.

PROPELLANT DETECTION: 100% mechanical and/or electrical detection of propellant levels within the cartridge

PACKAGING OPTIONS

- Carton
- Link